



Type	Lift	Load centre	mini			
			4		6	
	h3 mm	C mm	Capacity kg		Capacity kg	
			Max. lifting	At 3300 mm	Max. lifting	At 3300 mm
STANDARD	2900	500	400		600	
		600	350		500	
		700	300		410	
		800	270		350	
		1000	230		300	
DUPLEX with FREE LIFT	2850	500	390		570	
		600	340		470	
		700	300		390	
		800	260		330	
		1000	220		270	
TRIPLEX with FREE LIFT	4280	500	300	390	420	560
		600	280	330	350	460
		700	250	290	300	380
		800	220	250	250	310
		1000	170	210	210	260

Spostamenti Laterali / Side-Shift / Déplacement Latéral / Quesrchiebung / Desplazamientos laterales= **80+80 mm**

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverdindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.



Type	Lift	Load centre	MYCROS AC			
			8C		10C	
	h3 mm	C mm	Capacity kg		Capacity kg	
			Max. lifting	At 3300 mm	Max. lifting	At 3300 mm
STANDARD - DUPLEX with FREE LIFT	3300	500	800		1000	
		600	660		870	
		700	550		720	
		800	460		600	
		1000	370		510	
	3800	500	710	790	880	980
		600	600	650	740	830
		700	510	540	630	710
		800	430	450	510	590
		1000	340	360	400	490
	4200	500	610	780	800	970
		600	510	640	670	820
700		440	530	570	700	
800		390	440	480	580	
1000		310	350	380	480	
TRIPLEX with FREE LIFT	4350	500	560	700	700	940
		600	470	570	600	780
		700	400	460	490	640
		800	340	390	410	540
		1000	270	300	330	450
	4800	500	490	700	650	930
		600	420	570	540	780
		700	350	460	460	640
		800	300	390	390	540
		1000	240	300	300	450
	5700	500	400	690	540	920
		600	340	560	460	770
		700	300	450	380	630
		800	240	360	310	530
		1000	190	270	250	440

Spostamenti Lateral / Side-Shift / Déplacement Latéral / Quesrchiebung / Desplazamientos laterales= **80+80 mm**

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverdindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.



Type	Lift	Load centre	MYCROS AC							
			10				13			
			Capacity kg				Capacity kg			
			Cushion		Superelastic		Cushion		Superelastic	
h3 mm	C mm	Max. lifting	At 3300	Max. lifting	At 3300	Max. lifting	At 3300	Max. lifting	At 3300	
STANDARD - DUPLEX with FREE LIFT	3300	500	1000		1000		1300		1300	
		600	870		870		1043		1020	
		700	730		730		900		870	
		800	610		610		770		740	
		1000	520		520		650		610	
	3800	500	900	980	900	980	1180	1280	1160	1250
		600	760	830	760	830	1000	1030	970	1000
		700	650	710	650	710	840	890	820	850
		800	530	590	530	590	700	750	690	720
		1000	410	490	410	490	580	630	570	600
	4200	500	820	980	820	960	1050	1280	1000	1250
		600	690	830	690	810	900	1030	850	1000
700		590	710	590	670	770	890	720	850	
800		500	590	500	570	650	750	600	720	
1000		400	490	400	480	520	630	490	600	
TRIPLEX with FREE LIFT	4350	500	730	960	730	960	980	1250	890	1230
		600	620	810	620	810	880	1020	790	990
		700	520	670	520	670	750	880	670	850
		800	440	570	440	570	630	740	550	710
		1000	360	480	360	480	500	600	420	570
	4800	500	680	960	650	960	950	1250	850	1230
		600	570	810	540	810	800	1020	700	990
		700	490	670	460	670	680	880	580	850
		800	410	570	380	570	580	740	490	710
		1000	330	480	300	480	480	600	390	570
	5700	500	570	950	530	950	800	1230	690	1230
		600	490	800	450	800	700	990	590	980
		700	410	660	370	660	570	860	480	840
		800	340	560	300	560	490	720	400	700
		1000	270	470	230	470	400	580	310	560

Spostamenti Lateral / Side-Shift / Déplacement Latéral / Quesrchiebung / Desplazamientos laterales= **80+80 mm**

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverbindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.



Type	Lift	Load centre	MX16AC			
			Capacity kg		Capacity kg	
			Cushion		Superelastic	
			h3 mm	C mm	Max. lifting	At 3300 mm
STANDARD - DUPLEX with FREE LIFT	3300	500	1600		1600	
		600	1350		1350	
		700	1150		1150	
		800	990		990	
		1000	850		850	
	3800	500	1460	1550	1430	1520
		600	1240	1320	1220	1300
		700	1060	1120	1030	1100
		800	920	940	900	910
		1000	780	820	760	800
	4120	500	1330	1550	1310	1520
		600	1150	1310	1130	1290
700		990	1100	970	1090	
800		850	930	830	900	
1000		710	810	680	790	
TRIPLEX with FREE LIFT	4470	500	1300	1530	1280	1500
		600	1120	1290	1090	1270
		700	930	1080	900	1060
		800	780	890	750	870
		1000	640	790	610	770
	4800	500	1210	1500	1200	1470
		600	1030	1270	1000	1240
		700	850	1060	820	1030
		800	680	890	650	840
		1000	560	760	530	740
	5700	500	1050	1480	1030	1450
		600	900	1250	880	1220
		700	740	1030	720	1000
		800	600	870	580	850
		1000	510	750	490	720
	6180	500	850	1480	820	1450
		600	740	1240	710	1210
		700	630	1020	600	1000
		800	540	860	510	840
		1000	480	740	460	700

Spostamenti Laterali / Side-Shift / Déplacement Latéral / Quesrchiebung / Desplazamientos laterales= **100+100 mm**

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverbindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.



Type	Lift	Load centre	ME AC					
			6		8C		10C	
	h3 mm	C mm	Capacity kg		Capacity kg		Capacity kg	
			Max. lifting	At 3300 mm	Max. lifting	At 3300 mm	Max. lifting	At 3300 mm
STANDARD - DUPLEX with FREE LIFT	3300	500	600		800		1000	
		600	500		660		850	
		700	420		550		710	
		800	360		460		590	
		1000	300		370		500	
	3800	500	550	590	710	790	900	970
		600	460	490	600	650	750	810
		700	390	410	510	540	630	690
		800	325	350	430	450	510	570
		1000	240	290	340	360	400	470
	4200	500	450	580	610	780	800	970
		600	370	480	510	640	670	810
700		320	400	440	530	570	690	
800		285	340	390	440	490	570	
1000		210	280	310	350	390	470	
TRIPLEX with FREE LIFT	4350	500	470	560	580	720	720	950
		600	390	460	490	590	600	800
		700	330	380	420	480	500	650
		800	280	310	360	400	420	550
		1000	230	260	290	320	340	460
	4800	500	390	550	510	720	660	950
		600	325	450	435	590	550	790
		700	275	370	370	480	470	650
		800	230	310	320	400	390	550
		1000	180	260	260	310	310	460
	5700	500	320	540	420	710	540	940
		600	270	440	360	580	460	780
		700	220	360	315	470	380	640
		800	180	300	260	380	310	540
		1000	140	250	210	290	250	450

Spostamenti Laterali / Side-Shift / Déplacement Latéral / Quesrschiebung / Desplazamientos laterales= **80+80 mm**

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverbindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.



Type	Lift	Load centre	ME AC					
			8		10		12	
	h3 mm	C mm	Capacity kg		Capacity kg		Capacity kg	
			Max. lifting	At 3300 mm	Max. lifting	At 3300 mm	Max. lifting	At 3300 mm
STANDARD - DUPLEX with FREE LIFT	3300	500	800		1000		1200	
		600	670		870		950	
		700	560		730		810	
		800	490		610		670	
		1000	400		520		550	
	3800	500	750	780	900	980	1080	1180
		600	635	650	760	830	900	940
		700	540	540	650	710	740	800
		800	460	480	530	590	600	660
		1000	370	390	410	490	480	530
	4200	500	650	780	820	980	950	1180
		600	550	650	690	830	800	940
		700	460	540	590	710	670	800
		800	390	480	500	590	550	660
		1000	310	390	400	490	420	530
TRIPLEX with FREE LIFT	4350	500	620	720	730	960	900	1140
		600	530	590	620	810	800	920
		700	450	480	520	670	650	780
		800	380	410	440	570	540	640
		1000	310	340	360	480	420	500
	4800	500	550	720	680	960	860	1140
		600	470	590	570	810	700	920
		700	400	480	490	670	580	780
		800	340	410	410	570	480	640
		1000	210	340	330	480	380	500
	5700	500	490	720	570	950	720	1120
		600	420	590	490	800	600	910
		700	360	480	410	660	480	770
		800	300	410	340	560	390	630
		1000	170	340	270	470	300	490

Spostamenti Laterali / Side-Shift / Déplacement Latéral / Queschiebung / Desplazamientos laterales= 80+80 mm

IT: I dati indicati si intendono forniti a titolo indicativo e non impegnativo e si riferiscono all'allestimento standard.

EN: The specifications pointed out are not binding and they make reference to the standard configuration.

FR: Les spécifications indiquées sont sans engagement et elles se réfèrent à l'équipement standard.

DE: Die angegebene daten sind unverbindlich und sie betreffen die standardausrüstung.

ES: Los datos indicados son indicativos y sin compromiso y se refieren a la configuración estándar.